



**NOTES:**

1. CHAIN LINK FENCE HEIGHT TO BE AS SPECIFIED ON LANDSCAPE PLAN. BLACK VINYL WOVEN MESH TO BE 38x38MM, 9 GA. (INCL. VINYL) GALVANIZED STEEL CORE; MESH/FABRIC TO BE FASTENED TO TERMINAL POSTS WITH STRETCHER BARS AND BAR BANDS, 300 O.C.; SECURE TO RAILS WITH 3MM WIRE TIES, KNUCKLED, 457 O.C.
2. ALL FENCE POSTS AND RAILS TO BE GALVANIZED SCHEDULE 40 PIPE.
3. FINISH ON POSTS, TOP, BOTTOM, MIDDLE RAIL AND FITTINGS TO BE BLACK GLOSS ENAMEL BY POWDER COAT APPLICATION. ALL SURFACES TO BE CHEMICALLY CLEANED AND TREATED PRIOR TO COATING WITH PARKER BONDERITE AND CHLOROTHENE SOLVENT OR APPROVED EQUALS. POWDER COATING MUST BE A POLYESTER 2000 SERIES, THICKNESS OF 4-5 MILS BY ELECTROSTATIC PROCESS, OVEN-CURED TO A SMOOTH AND EVEN SURFACE.
4. PLASTIC COUPLINGS, FITTINGS OR ANY OTHER PLASTIC COMPONENTS WILL NOT BE ACCEPTED.
5. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.

CHAIN LINK FENCE  
A-1220, B-1830



**L830**

N.T.S

SEPTEMBER 2014

SITE AMENITIES - SERIES 800