



**NOTES:**

1. POLE, FITTINGS AND ALL ACCESSORIES OF THE SAFETY STATION WILL BE PROVIDED TO THE CONTRACTOR BY THE CITY. THE CONTRACTOR WILL INSTALL THE POLE AND ACCESSORIES AS SHOWN.
2. FINISH OF POLE AND ALL OTHER STEEL COMPONENTS AND FITTINGS TO BE SAFETY YELLOW GLOSS ENAMEL POWDER COAT APPLICATION. PRIOR TO POWDER COATING, ALL SURFACES TO BE CHEMICALLY CLEANED AND TREATED WITH PARKER BONDERITE AND CHLOROTHENE SOLVENT OR APPROVED EQUAL. POWDER COATING MUST BE A POLYESTER 2000 SERIES APPLIED IN A THICKNESS OF 4-5 MILS BY ELECTROSTATIC COAT AND OVEN, CURED TO A SMOOTH AND EVEN SURFACE.
3. NO PLASTIC COMPONENTS ARE TO BE USED EXCEPT WHERE NOTED.
4. PROVIDE MINIMUM 2 STATIONS FOR SWM POND AT 200 M APART.
5. SAFETY STATION REQUIRED AT VALLEY BRIDGE.
6. FOR PARK / VALLEYLAND WHERE WALKWAYS ARE 5 M OR LESS. SAFETY STATION REQUIRED AT 200 M APART.
7. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.