



NOTES:

1. FOUNTAIN MODEL TO BE: KASKO 3.1 JF 3HP DECORATIVE FLOATING FOUNTAIN BY RITTENHOUSE ST. CATHARINES, ON (1.800.461.1041) OR APPROVED EQUIVALENT. FOUNTAIN PACKAGE IS TO INCLUDE 240 V CONTROL PANEL.
2. INSTALL FOUNTAIN UNIT AND ANCHORS AS PER MANUFACTURER'S INSTRUCTIONS.
3. ELECTRICAL REQUIREMENTS TO BE SPECIFIED BY LICENSED ELECTRICAL CONSULTANT WHO IS A REGISTERED PROFESSIONAL ENGINEER LICENSED IN ONTARIO.
4. ELECTRICAL SPECIFICATIONS MUST BE SPECIFIC TO EACH APPLICATION. ALL WORK MUST BE IN ACCORDANCE WITH THE ONTARIO ELECTRICAL SAFETY CODE, 24TH EDITION (2009).
5. CONTROL PANEL METAL ENCLOSURE TO BE PAD LOCKED. REFER TO ELECTRICAL DRAWINGS FOR SPECIFICATIONS.
6. ELECTRICAL CONSULTANT TO SPECIFY REQUIRED POWER CORD LENGTH.
7. MINIMUM OPERATING WATER DEPTH FOR THIS FOUNTAIN MODEL IS 600 MM.
8. THIS FOUNTAIN MODEL INCLUDES SIX DIFFERENT SPRAY NOZZLES FOR DIFFERENT SPRAY EFFECTS. CONSULT WITH CITY STAFF FOR NOZZLE SELECTION.
9. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.