



APPLICATION REQUIREMENTS
 1-No Direct Frontage
 2-Posted Speed Limit is greater than 50km/hr
 3-Truck % is greater than 2%

ITEM	15m	0m
MULTI USE PATH	14.25m	0.75m
MULTI USE PATH	11.25m	3.75m
LIGHTPOLE	11.0m	4.0m
JOINT USE TRENCH	9.85m	5.15m
UTILITY BOX	8.95m	6.05m
JOINT USE TRENCH	8.85m	6.15m
HYDRANT	8.25m	6.75m
UTILITY BOX	7.25m	7.25m
WATERMAIN	6.75m	8.25m
EDGE OF PAVEMENT	6.0m	9.0m
STORM SEWER	0.5m	14.5m
C/L R.O.W.	0.00m	15m
C/L ROAD	1.0m	14.0m
SANITARY SEWER	2.5m	12.5m
EDGE OF PAVEMENT	8.0m	7.0m
WATERMAIN	8.75m	6.25m
UTILITY BOX	9.75m	5.25m
HYDRANT	10.25m	4.75m
JOINT USE TRENCH	10.35m	4.65m
UTILITY BOX	10.95m	4.05m
JOINT USE TRENCH	11.32m	3.68m
SIDEWALK	13.12m	1.88m
LIGHTPOLE	13.32m	1.68m

NOTES:

1. LOCAL SOIL CONDITIONS MAY REQUIRE CHANGES IN THE DEPTHS OF MATERIAL TO BE PLACED.
2. WATERMAIN MAY BE LOCATED ON EITHER BLVD.
3. FOR JOINT USE TRENCH DETAILS, SEE STD. No. 345.
4. BOULEVARD TO HAVE 150 mm OF TOPSOIL AND 50 mm OF SOD.
5. MINIMUM PAVEMENT STRUCTURE TO BE AS FOLLOWS:
 40 mm HL3 ASPHALT (High Stability or HLI)
 85 mm HL8 ASPHALT (100 mm FOR ALL NEW SUBDIVISION ROADS)
 150 mm GRANULAR "A" OR 130 mm OF 20 mm CRUSHER RUN LIMESTONE
 450 mm GRANULAR "B" OR 350 mm OF 50 mm CRUSHER RUN LIMESTONE
6. THE LOCATION OF THE LIGHTPOLE WILL DEPEND ON THE DESIGN SPEED AS OUTLINED IN THE ROADSIDE SAFETY MANUAL.
7. 1.8m SIDEWALKS MAY BE REPLACED WITH A 3.0m MULTI USE PATH.
8. LANE WIDTHS CAN VARY SUBJECT TO ENVIRONMENTAL ASSESSMENT OR COMMISSIONER APPROVAL.
 ANY REDUCTION IN LANE WIDTH WILL NOT REDUCE THE RIGHT OF WAY REQUIREMENTS.



BRAMPTON
 Flower City
 brampton.ca

APPROVED:
 2019/07/02

MAJOR COLLECTOR

14.0m PAVEMENT
 ON 30.0m R.O.W.
 With Multi-use Pathway On Side

ORIGINAL:
 2010/09/16

REV. 3

203

N.T.S