



12/C #14 MTO RUNNER CABLE			
COND #	COLOUR/MARK	CABLE GROUP 1	CABLE GROUP 2
1	WHITE	NEUTRAL	NEUTRAL
2	BLACK	NOTE 1	NOTE 1
3	ORANGE	NOTE 1	NOTE 1
4	RED /"RED ONE"	MAIN STREET RED	MAIN STREET RED
5	RED /"RED TWO"	SIDE STREET RED	SIDE STREET RED
6	RED /"RED THREE"	SPARE	SPARE
7	YELLOW/"AMBER ONE"	MAIN STREET AMBER	MAIN STREET AMBER
8	YELLOW/"AMBER TWO"	SIDE STREET AMBER	SIDE STREET AMBER
9	YELLOW/"AMBER THREE"	NOTE 1	NOTE 1
10	BLUE/"GREEN ONE"	MAIN STREET GREEN	MAIN STREET GREEN
11	BLUE/"GREEN TWO"	SIDE STREET GREEN	SIDE STREET GREEN
12	BLUE/"GREEN THREE"	NOTE 1	NOTE 1

NOTES

- WHERE ARROW ADVANCE GREENS ARE USED, USE COND. #12, BLUE/"GREEN THREE" AND COND. #9, YELLOW/"AMBER THREE" FOR THE MAIN STREET AND COND. #2, BLACK AND COND. #3, ORANGE FOR THE SIDE ROAD HEADS.
- CONNECTIONS SHOWN ARE GENERAL AND TYPICAL AND SHALL BE ADJUSTED TO SUIT THE INTERSECTION LAYOUT.
- THE SYSTEM SHOWN REQUIRES CONDUITS ALL AROUND THE INTERSECTION.
- ALL SIGNAL HEAD RUNNER CABLE SHALL BE AS PER OPSS 2409 AND/OR CONTRACT SPECIFICATIONS.

ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED



APPROVED:
APRIL 2014

TRAFFIC SIGNALS
TYPICAL 2 TO 8 PHASE WIRING
WITH 12/C CABLE

ORIGINAL:
TRAFFIC DETAILS - SERIES 400 APRIL 2014

REV. 1

441

N.T.S