



**NOTES:**

1. THE HEIGHT OF THE STOCKPILE MATERIAL SHALL NOT EXCEED 5.0m.
2. THE SIDE-SLOPE OF THE STOCKPILE SHALL NOT EXCEED 2:1.
3. THE LIMIT OF PILES OF TOPSOIL SHALL BE LOCATED A MINIMUM OF 15m FROM A ROADWAY, WATERWAY AND/OR WATERBODY.
4. THE BOTTOM OF THE STOCKPILE SHALL BE LOCATED A MINIMUM DISTANCE OF 8.0m FROM THE PROPERTY LINE/SITE ALTERATION LIMIT, WHICHEVER IS MOST CONSERVATIVE.
5. A SWALE ("V" CHANNEL) SHALL BE PROVIDED AT THE TOE OF THE STOCKPILE SLOPE TO INTERCEPT SEDIMENT.
6. STOCKPILES ARE TO BE LOCATED OUTSIDE OF THE REGULATORY FLOODPLAIN LIMIT OR AS DIRECTED BY THE CITY AND CONSERVATION AUTHORITY.
7. STOCKPILES LEFT IN PLACE FOR MORE THAN 30 DAYS TO BE VEGETATED BY SEEDING OR APPROVED EQUIVALENT.

ALL DIMENSIONS ARE SHOWN IN MILLIMETERS UNLESS OTHERWISE SHOWN