



NOTES:

1. FOR LUMINAIRE DETAILS REFER TO CITY STANDARD DRAWING #527.
2. FOR POLE BRACKET DETAIL REFER TO CITY STANDARD DRAWING #528.
3. FOR POLE DETAIL REFER TO CITY STANDARD DRAWING #531 AND #532
4. METALLIC HANDHOLE FRAME MUST BE ELECTRICALLY BONDED TO THE #6 GROUND WIRE. C/W TAMPERPROOF SCREWS AND ANTI-SEIZE COMPOUND
5. INSTALLATION DEPTH IS 10% OF POLE HEIGHT PLUS 610mm
6. 50mm FLEXIBLE PVC CONDUIT TO PROTECT CABLE AT POLE APERTURE MINIMUM 60mm OF FLEX CONDUIT TO BE FED INTO POLE SEE FIGURE A

ALL DIMENSIONS IN mm UNLESS OTHERWISE NOTED



**BRAMPTON**  
Flower City

**DECROATIVE POLE  
INSTALLATION**

9.9m & 12.2m TYPICAL INSTALLATION  
ON TENON MOUNT CONCRETE POLE

STREET LIGHT DETAILS - 500

APPROVED:  
MARCH  
2017

ORIGINAL:  
JUNE 2006

REV. 1

**530**

N.T.S